

### TK104 Seashell

### Brushed & Colour UV Oiled Natural Oak Plank



#### **Product Details**

Product Code	TK104
Collection	Tundra
Construction	Engineered
Species	Oak
Product Type	Engineered Plank
Surface	Brushed
Finish	Stained & UV Cured Oil
Dimensions	W 190 x D 15 x L 1700 - 2000 mm
Top Layer	4 mm – Solid European Oak
Core Layer	11 mm – 2 Layer Soft wood
Grade	CD Rustic
Pack Size	May vary depending on enclosed plank length
Pack Contents	May vary depending on enclosed plank length
Joint Type	Tongue & Grooved
Edge Profile	Bevel Edged on 4 sides

#### **Technical Information**

UKTR / UK Timber Regulation	Full documented evidence of legality of timber
FSC® Certification	FSC 100% Certified
PEFC® Certification	Not available with this product
Janka Hardness	Oak 1360 lbf (6000N)
Slip Resistance	EN 14231 (Test Result 58/42 PTV)
European Reaction to Fire Classification	EN 13501-1 (test result Dfl-s1)
Release of Formaldehyde	EN 717-1 (Test result E1)
Thermal Conductivity	EN 12524 (Test result: 0.16W/mK)

## **Grading: Rustic**

Rustic Floors can contain varying size live and filled dead knots, colour variation, sapwood, heartwood and end-checks (filled splits).

V4 Wood Flooring is chosen for its natural beauty, therefore grading criteria is always an approximation as every piece of timber is different. If further selection is needed, please allow for extra material upon installation

#### Installation Methods

All V4 floors should be installed by experienced flooring installers who have read and understood the appropriate installation guides at www.v4woodflooring.co.uk

Fully Bonded	Yes*
Secret Nailed	No
Floated on Underlay	No
Over Underfloor Heating	Yes* (fully bonded installation recommended)

#### **Maintenance Schedule Advice**

Avoid scratches by minimising grit and dust, install doorway entrance mats and felt pads to protect furniture. Use PH neutral cleaners and avoid soaking the floor with water. For more detailed advice visit www.v4woodflooring.co.uk



The mark of responsible forestry

# V4 Wood Flooring®

\*Subject to correctly prepared and compatible subfloor and in conjunction with correct installation