

ZB201 Smoked Oak

Smoked, Brushed & UV Oiled Rustic Oak Bevel Edge Block



Technical Information

Full documented evidence of legality of timber FSC® Certification FSC®100% (TT-COC-004200) PEFC® Certification Not available with this product Janka Hardness Oak 1360 lbf (6000N) Slip Resistance EN 14231 (Test Result 64/32 PTV) European Reaction to Fire Classification Release of Formaldehyde EN 717-1 (Test result E1) Thermal Conductivity EN 12524 (Test result: 0.16W/mK) Tog Rating 1.13	1 00111110di IIIIOI111diioi	
PEFC® Certification Janka Hardness Oak 1360 lbf (6000N) Slip Resistance EN 14231 (Test Result 64/32 PTV) European Reaction to Fire Classification Release of Formaldehyde EN 717-1 (Test result E1) Thermal Conductivity Not available with this product EN 1350 lbf (6000N) EN 14231 (Test Result 64/32 PTV) EN 13501-1 (test result Dfl-s1) EN 12524 (Test result: 0.16W/mK)	UKTR / UK Timber Regulation	
Janka Hardness Oak 1360 lbf (6000N) Slip Resistance European Reaction to Fire Classification Release of Formaldehyde EN 13501-1 (test result Dfl-s1) Thermal Conductivity EN 12524 (Test result: 0.16W/mK)	FSC® Certification	FSC [®] 100% (TT-COC-004200)
Slip Resistance EN 14231 (Test Result 64/32 PTV) European Reaction to Fire Classification EN 13501-1 (test result Dfl-s1) Release of Formaldehyde EN 717-1 (Test result E1) Thermal Conductivity EN 12524 (Test result: 0.16W/mK)	PEFC® Certification	Not available with this product
European Reaction to Fire Classification Release of Formaldehyde EN 717-1 (Test result E1) Thermal Conductivity EN 12524 (Test result: 0.16W/mK)	Janka Hardness	Oak 1360 lbf (6000N)
Classification EN 13501-1 (test result D11-S1) Release of Formaldehyde EN 717-1 (Test result E1) Thermal Conductivity EN 12524 (Test result: 0.16W/mK)	Slip Resistance	EN 14231 (Test Result 64/32 PTV)
Thermal Conductivity EN 12524 (Test result: 0.16W/mK)	•	EN 13501-1 (test result Dfl-s1)
· · · · · · · · · · · · · · · · · · ·	Release of Formaldehyde	EN 717-1 (Test result E1)
Tog Rating 1.13	Thermal Conductivity	EN 12524 (Test result: 0.16W/mK)
	Tog Rating	1.13

Grading: Rustic

Rustic Floors can contain varying size live and filled dead knots. Colour variation, sapwood, heartwood and end-checks (filled splits).

V4 Wood Flooring is chosen for its natural beauty, therefore grading criteria is always an approximation as every piece of timber is different. If further selection is needed, please allow for extra material upon installation.

Product Details

Product Code	ZB110
Collection	Deco Parquet
Construction	Engineered
Species	Oak
Product Type	Engineered Parquet Block
Surface	Smoked, Brushed & Stained
Finish	Matt Lacquer
Dimensions	90 x 14/3 x 360 mm
Top Layer	3 mm – Solid European Oak
Core Layer	11 mm – Multi-Layer Eucalyptus & Poplar
Grade	Rustic
Pack Size	1.8144 m ²
Pack Contents	56 Boards
Joint Type	3 Grooves 1 Tongue
Edge Profile	Bevel Edged on 4 sides

Installation Methods

All V4 floors should be installed by experienced flooring installers who have read and understood the appropriate installation guides at www.v4woodflooring.co.uk

Fully Bonded	Yes*
Secret Nailed	No
Floated on Underlay	No
Over Underfloor Heating	Yes* (fully bonded installation recommended)

Maintenance Schedule Advice

Avoid scratches by minimising grit and dust, install doorway entrance mats and felt pads to protect furniture. Use PH neutral cleaners and avoid soaking the floor with water. For more detailed advice visit www.v4woodflooring.co.uk



The mark of responsible forest

*Subject to correctly prepared and compatible subfloor and in conjunction with correct installation

V4 Wood Flooring®

This technical data sheet was written by 1/4 Ward Flooring Ltd. Creenbey

© This technical data sheet was written by V4 Wood Flooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.