

EBL207 RAW UMBER



٢	ro	a	uC	ιD	eı	all	S

Product Code	EBL207		
Collection	European Boutique - Lineage		
Construction	Engineered		
Species	Oak		
Product Type	Engineered Plank		
Surface	Smooth Sanded		
Finish	Osmo Hardwax Oil		
Available Dimensions	190 x 15/4 x 700-2400 mm 225 x 20/5 x 700-2400 mm		
Top Layer	Solid European Oak		
Core Layer	Multi-Layer Birch Ply		
Available Grade(s)	Rustic / Select		
Pack Size	N/A		
Pack Contents	Random		
Joint Type	Tongue & Grooved		
Edge Profile	Bevel Edged on 2 sides		

EUTR/ European Timber Regulation	Timber manufactured in the EU.		
FSC® Certification	Not available with this product		
PEFC® Certification	Available on Request		
Janka Hardness	Oak 1360 lbf (6000N)		
Slip Resistance	EN 14342:2013: (NPD)		
European Reaction to Fire Classification	EN 14342:2013: 15mm (test result Dfl-s1) 20mm (test result Cfl-s1)		
Release of Formaldehyde	EN 14342:2013: (Test result E1 (≤0.015mg/m³		
Tog Rating	15mm 1.13 20 mm 1.2		

Grading: Rustic

Bigger rustic circular open filled knots, cross-shaped and other shaped knots unlimited and cracks filled allowed. Closed healthy knots unlimited, in principal no sapwood allowed, no pinholes, insects or molding mistakes, combed grain and different grain flow occasionally permitted, mineral streaks can occur in small amount due to influence oxidative natural process

Grading: Select

Dot-sized knots (practically knot-free), no Sapwood, no pinholes, no insects or surface molding mistakes, natural color variations are allowed, combed grain and different grain flow occasionally permitted, mineral streaks can occur in small amount due to influence oxidative natural process

Installation Methods

All V4 floors should be installed by experienced flooring installers who have read and understood the appropriate installation guides at www.v4woodflooring.co.uk

Fully Bonded	Yes*		
Secret Nailed	No		
Floated on Underlay	Yes*		
Over Underfloor Heating	Yes* (fully bonded installation recommended)		

Maintenance Schedule Advice

Avoid scratches by minimising grit and dust, install doorway entrance mats and felt pads to protect furniture. Use PH neutral cleaners and avoid soaking the floor with water. For more detailed advice visit www.v4woodflooring.co.uk





Technical Information

Country of Manufacture Czech Republic

V4 Wood Flooring®

*Subject to correctly prepared and compatible subfloor and in conjunction with correct installation

Call +44(0)1276 488099 Email team@v4woodflooring.co.uk Visit www.v4woodflooring.co.uk © This technical data sheet was written by V4 Wood Flooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.